

SikaCim® Pink

Liquid integral waterproofing compound for concrete, mortar and plaster

Construction

Product Description	Specially formulated unique pink coloured liquid integral water proofing compound for concrete, mortar and plaster based on Sika's technology of special selective polymers , surface active agents and additives.
Uses	SikaCim® Pink water proofing of concrete and mortars used for <ul style="list-style-type: none">■ Roof Slabs and screed■ Basement■ Water tank & water retaining structures■ Bath rooms and balconies■ External plastering■ Repair and renovation■ Sumps and drains
Characteristics / Advantages	<ul style="list-style-type: none">■ Compatibility - Easily dispersible and compatible with all varieties of Portland Cement including Slag Cement■ Cohesiveness - Minimizes loss of mortar due to rebound in plastering jobs, hence great ease of application and saving■ Economical - Required at a very small dosage■ Low Permeability - Improves water tightness to a great extent■ Water Reducer - Helps in reducing the water content■ Workability - Improves workability without increased water content■ Shrinkage - Reduced shrinkage cracks in concrete & mortar, better finish■ Durability - Acts to disrupt the leakage causing capillary structures formed in concrete making it water tight and durable■ Strength – Helps in enhancing the strength■ Corrosion resistant- Makes concrete more cohesive and water tight hence protects steel better against corrosion■ Increase Productivity – Less time is required for plastering hence saving on labor cost per sq foot■ Packing - Supplied in consumer friendly packs easy to handle
Tests	
Approvals/Standards	IS 9103 & IS 2645
Product Data	
Form	
Appearance / Colour	Pink Color Hazy Liquid
Packaging	100gm Sachet & 1kg,5kg,20kg HDPE Container



Storage

Storage Conditions / Shelf-Life Best before 24 months from date of production if stored properly in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +10°C and +40°C. Protect from direct sunlight and frost.

Technical Data

Specific Gravity ~1.21 at 25°C

pH ≥ 6

System Information

Application Details

Consumption / Dosage 100g for 50kg bag of cement (0.2% by weight of cement)

Application Instructions

- Dispensing**
- Charge cement, aggregates and sand for concrete/ cement and sand for mortar and dry mix for 1 minutes
 - Add 50-70 % of required water and mix t for 2-3 minutes
 - Add required quantity of SikaCim® Pink to the remaining water and pour it in the mixing drum and mix the entire quantity for approx. 3 minutes to achieve homogenous mix
 - Pour the mixture on a tray and use as per requirement and lay the concrete
 - Cure as per normal procedure by ponding/ curing compound (Antiso® EWP)

Cleaning of Tools Clean all tools and application equipment with water immediately after use. Hardened / cured material can only be mechanically removed.

Value Base All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Health and Safety Information For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal Notes The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Registered office:

Sika India Pvt. Ltd.
Commercial Complex II
620, Diamond Harbour Road
Kolkata, 700 034, India

Phone +91 33 2447 2448/2449
Telefax +91 33 2397 8688
ind.sika.com
info.india@in.sika.com